



Talent & Tradition

*The Hercules IP*



Our plug and play internet *Hercules IP* takes the *Hercules Plus* technology to the next level, allowing Dial Up and IP ATMs to connect to the Internet via connection directly to a router, switch, through a WiFi adapter or our AC Powerline Kit, replacing costly phone line installations and installation scheduling delays.



### ***Hercules IP Product Functionality***

- Dial up ATMs to Internet for Cash Dispensing ATMs.
- Internet enabled ATMs to Internet for Cash Dispensing ATMs.

### ***Hercules IP Generated Cost Decreases***

- Eliminated phone line installation delays and reduced phone line costs.
- Eliminated long distance transaction charges.
- No activation fees.
- Unlimited Transactions.

### ***Hercules IP Generated Benefits***

- No per Mbyte charges.
- Decreased transaction time.
- Enables use of ATM Manufacture's Software to remotely manage your ATM transactions.
- No long term contracts required, month to month service.
- Plug and Play Dial / IP ATM to IP.
- WiFi can be used to eliminate cables.
- No static IP required.
- Immediate ATM Deployment.

### ***Hercules IP Generated Security***

- Triple DES secure communications.
- Free communication failure alerts via Text to Cell and Email.
- Optional AC Disconnect Modules available (see below).
- Optional Anti-Theft Modules available (see below).
- Optional Alarm Module available (see below).



### **Security Monitoring 24/7 (with optional Anti-Theft Kit)**

With this optional kit, Hercules watches your ATM constantly and sends security alerts via cell phone data message and e-mail to you and/or whoever else you designate immediately, on the following conditions:

1. Power Disconnected
2. Machine Tilted
3. Door Opened

### **AC Disconnect Module**

ATMs require occasional resetting, but what happens if you have a unit in a remote location, miles away and inconvenient for you to do so? This optional accessory will allow you to reset your ATM machine remotely merely by sending a signal through the DPL Wireless website to your Hercules unit to reboot the ATM saving both your valuable time and money.

### **Specifications**

Dial In Interface:	Central Office POTS Line, RJ-11, 2400 baud v.22bis or 1200 baud
InterfacePort:	Custom port for anti-theft harness which is optional
Protocols Supported:	VISA-2, Security Encoding: Triple DES
Network Services:	DHCP enabled internet connection
Power Supply Output:	12 VDC, 2A, Center Positive, 5.5mm x 2.1mm
Power Supply Input:	120 VAC, 60 Hz, 14W, Circuit-Test RP-091A-P (105-130 VAC range)
Dimensions (h x w x d):	3.8 x 12.2 x 14.5cm (1.5 x 4.8 x 5.7 inches)
Operating Temp:	-10 to 45 °C (14 to 113 °F)
Weight:	1.1 kg (2.4 lbs.)
Warranty:	2 years parts and labour